

USB Device an einen Container durchreichen

```
[code bash] (root@n1-pve-cluster marko) > lsusb Bus 002 Device 002: ID 8087:8000 Intel Corp. Bus 002 Device 001: ID 1d6b:0002 Linux Foundation 2.0 root hub Bus 001 Device 002: ID 8087:8008 Intel Corp. Bus 001 Device 001: ID 1d6b:0002 Linux Foundation 2.0 root hub Bus 004 Device 001: ID 1d6b:0003 Linux Foundation 3.0 root hub Bus 003 Device 002: ID 0403:6001 Future Technology Devices International, Ltd FT232 Serial (UART) IC Bus 003 Device 001: ID 1d6b:0002 Linux Foundation 2.0 root hub [/code]
```

```
[code bash] (root@n1-pve-cluster marko) > udevadm info -a -n /dev/ttyUSB0 | grep '{serial}' | head -n1 [/code]
```

```
[code bash] vim /etc/udev/rules.d/98-RFXtrx-CUL.rules
```

```
SUBSYSTEMS=="usb", KERNEL=="ttyUSB*", ATTRS{idProduct}=="6001",  
ATTRS{idVendor}=="0403", SYMLINK+="RFXCOM_RFXtrx433_A1XEABQO", MODE=="0666",  
GROUP=="dialout" [/code]
```

From:
<https://blog.cooltux.net/> - TuxNet DokuWiki

Permanent link:
https://blog.cooltux.net/doku.php?id=it-wiki:proxmox:usb_passthrough&rev=1583393834

Last update: **2020/03/05 07:37**

